



Klemmsan®

270830 KPR-SCE-60VAC/DC-1C

1 C/O PLC Relay

Input	Nominal Voltage (Un)	60VAC/DC
	Operating Voltage Range	$(0.8 - 1.15) \times U_n$
	Release Voltage	$0.2 \times U_n$
	Integrated RCZ Filter	—
Power Consumption	AC	<0.4VA
	DC	<0.3W
Contact Characteristic	Type	1 C/O (SPDT)
	Material	AgSnO ₂
	Coil Voltage	60VDC
	Coil Impedance	16600(1±15%)Ω
	Coil Consumption	210mW
	Operate Time	Maks. 10ms
	Release Time	Maks. 5ms
	Max. Ratings - AC	6A/250VAC;1500VA
	Max. Ratings - DC	6A/30VDC;180W
Mechanical Lifetime	NO	$\geq 10^7$ operations
Electrical Lifetime Operations (UL approval, 85°C)	NO	3×10^4 operations
	NC	1×10^4 operations
Dielectric Strength	Between Relay Coil and Contacts	4000VAC 1 min.
	Between Contacts	1000VAC 1 min.

Ambient Conditions	Operating Temperature	-40°C +85°C
	Storing Temperature	-40°C +85°C
	Relative Humidity (No Condensation)	5% - 85%
Certificates	UL508, IEC EN 61984-2011, IEC EN 61947-1:2010	✓
Socket	Type	KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET),KPR-SCE-60VAC/DC-1C (RELAY SOCKET)
	Definition	PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC),PLC RELAY SOCKET (60VAC/DC)
	Order Number	270 831,270 831,270 831,270 831,270 831,270 831,270 831,270 831
	Packing Units	10,10,10,10,10,10,10
Relay	Type	Slim Type 60VDC Relay
	Definition	Relay for 270 830 and 270 831
	Order Number	095 040
	Packing Units	10 pcs.
Plug-In Bridge 16	Type	TK-KPR-S (KPR-SCE BRIDGE/16)
	Definition	Plug - in bridge for 16 hole
	Order Number	476 605
	Packing Units	25 pcs.
Plug-In Bridge 8	Type	TK-KPR-S (KPR-SCE BRIDGE/8)
	Definition	Plug in bridge - 8
	Order Number	476 606
	Packing Units	50 pcs.
Plug-In Bridge 2	Definition	—
	Order Number	—
	Quantity	
	Type	—
Dekafix	Type	DG 10/6T
	Definition	Terminals Labels for interface relays
	Order Number	505 390
	Packing Units	360

Avrupa standartlarına uygunluk belgesi - CE Certificate

PLC General Product Information

Order Info

┌ 270830 1 C/0 PLC Relay

© 2019 Klemsan A.Ş.
www.klemsan.com