

# Ball valve VZBE-1/4-T-63-D-2-M-V15V15

Part number: 4745214

FESTO



## Data sheet

Feature	Value
Type code	VZBE
Seat seal material	PTFE
Design	2-way ball valve with hand lever
Actuation type	Mechanical
Sealing principle	Soft
Mounting position	Any
Type of mounting	Line installation
Fitting connection	1/4 NPT
Switching position indication	Slot direction = flow direction
Inside diameter	11.6 mm
Nominal width DN	8
Valve function	2/2
Flow direction	Reversible

Feature	Value
Nominal pressure of fitting PN	63
Breakaway torque at differential pressure, nominal pressure, fitting PN	3.5 Nm
Based on norm	ASME B1.20.1
Symbol	00991458
Medium	Compressed air as per ISO 8573-1:2010 [---] Neutral liquids Vapor Water Inert gas
Temperature of medium	-20 °C ... 200 °C
Flow rate Kv	5 m³/h
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Housing material	Cast stainless steel
Material number of housing	1.4408
Seals material	PTFE
Ball material	Cast stainless steel
Material number for ball	1.4408
Shaft material	High-alloy stainless steel
Material number for shaft	1.4401
Product weight	200 g
Certification	CRN
Corrosion resistance class (CRC)	3 - High corrosion stress