


Ball valve VZBE-2-T-63-F-3T-F0507-V15V15

Part number: 4834303

FESTO



Data sheet

Feature	Value
Type code	VZBE
Seat seal material	PTFE
Design	3-way ball valve Drilled T hole
Actuation type	Mechanical
Sealing principle	Soft
Mounting position	Any
Type of mounting	Line installation
Fitting connection	2 NPT
Switching position indication	Slot direction = flow direction
Flange hole pattern	F0507
Inside diameter	38.1 mm
Nominal width DN	50
Valve function	3/2
Flow direction	Reversible
Nominal pressure of fitting PN	63
Breakaway torque at differential pressure, nominal pressure, fitting PN	85 Nm
Based on norm	ISO 5211 ASME B1.20.1
Symbol	00991888
Medium	Neutral liquids Vapor Inert gas Compressed air as per ISO 8573-1:2010 [-:-:-] Water
Temperature of medium	-20 °C ... 200 °C
Flow rate Kv type T corner	22.5 m³/h
Note on materials	RoHS-compliant Contains paint-wetting impairment substances
Housing material	Cast stainless steel
Material number of housing	1.4408

Feature	Value
Seals material	PTFE
Ball material	Cast stainless steel
Material number for ball	1.4408
Shaft material	High-alloy stainless steel
Material number for shaft	1.4401
Product weight	5560 g
Certification	CRN
CE marking (see declaration of conformity)	as per EU pressure equipment directive
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress