

Ball valve VAPB-2-F-25-F05

Part number: 534309

FESTO



Data sheet

Feature	Value
Type code	VAPB
Design	2-way ball valve
Actuation type	Mechanical
Sealing principle	Soft
Mounting position	Any
Type of mounting	Line installation
Fitting connection	Rp2
Switching position indication	Slot direction = flow direction
Flange hole pattern	F05
Nominal width DN	50
Flow direction	Reversible
Nominal pressure of fitting PN	25

Feature	Value
Breakaway torque at differential pressure, nominal pressure, fitting PN	29 Nm
Breakaway torque at 10 bar differential pressure	22 Nm
Based on norm	ISO 5211
Symbol	00991458
Medium	Water Neutral liquids Inert gas Compressed air as per ISO 8573-1:2010 [-:-:-]
Temperature of medium	-20 °C ... 150 °C
Flow rate Kv	292 m³/h
Note on materials	RoHS-compliant Contains paint-wetting impairment substances
Housing material	Brass Nickel-plated
Material number of housing	CW617N
Seals material	HNBR PTFE
Ball material	Brass Hard-chrome-plated
Material number for ball	CW617N
Shaft material	Brass
Material number for shaft	CW614N
Product weight	3100 g
CE marking (see declaration of conformity)	as per EU pressure equipment directive
Corrosion resistance class (CRC)	1 - Low corrosion stress