

AS-i module CESA-GW-AS-PB

Part number: 567032

FESTO



Data sheet

Feature	Value
Dimensions W x L x H	75 mm x 120 mm x 83 mm
Type code	CESA
Control elements	4 pushbuttons
Status indications	Green LED voltage ON LED green: PROFIBUS master detected LCD display LED yellow: planning mode LED green AS-i voltage OK LED red: configuration error LED green: slave programming Green LED normal AS-i operation
Operating voltage	AS-i voltage 30 V DC
Current consumption	200 mA from the AS-i circuit
CE marking (see declaration of conformity)	As per EU EMC directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-25 °C ... 85 °C
Degree of protection	IP20
Ambient temperature	0 °C ... 55 °C
Resistance to shock	as per EN 61131-2
Resistance to vibration	as per EN 61131-2
Certification	c UL us - Listed (OL) C-Tick
Product weight	460 g
Fieldbus interface, transmission rate	9.6 kbit/s to 12 Mbit/s
Fieldbus interface, connection technology	Sub-D 9-pin Socket
Fieldbus interface, type	Profibus as per DIN 19245 part 3
Programming/diagnostic interface	Serial interface RS 232
Note on materials	RoHS-compliant Contains paint-wetting impairment substances
Housing material	High-alloy stainless steel