



Klemsan®

601400 ETOR-4

Ethernet Gateway (TCP/IP - RS485)

General		
	Casing Width (mm)	17,5
	Connections	Screw Terminal (for supply and serial interface)
	Working Mode	Server or Client Selectable (bidirectional)
	Configuration	Mini USB Port or Web Interface
	DHCP (Automatic IP Receive)	✓
	ARP	✓
	Ping Blocking	✓
	LED Indicators	✓
	Reset Function	✓
	ESD Protection	✓
	Driver Supported	Microsoft .NET Framework 3.5 üzeri windows işletim sistemleri
Ethernet Interface		
	Number of Ports	1
	Operation Modes	Modbus TCP, Modbus RTU over TCP, Modbus ASCII over TCP
Number of Remote Connections		
	Server Mode	6
	Client Mode	1
Ethernet Interface		
	Connector	RJ45
	Data Transmission Rate	10/100 Base-TX
Serial Interface		
	Number of Ports	1
	Operation Modes	Modbus RTU, Modbus ASCII
	Serial Standart	RS485
Number of Serial Devices		
	Server Mode	64
	Client Mode	1

Serial Communication Parameters	Baud Rate	300 to 115200 bps
	Data Bit	8
	Stop Bits	1 or 2
	Parity	None, Even, Odd
Voltage	AC	18-50V
	DC	18-50V
Consumption	AC	<2.2VA
	DC	<1.2W
Supply	Frequency	45-65Hz
Galvanic Isolation	Supply - Ethernet Port	1500VRMS, 2250VDC
	Supply - Serial Port	1500VRMS, 2250VDC
	Serial Port - Ethernet Port	2500VRMS
Mechanical Properties	Weight (g)	58
	Packing Unit	1
	Protection Class	IP20
	Assembly Type	Rail Mount
Ambient Conditions	Operating Temperature	-10°C +60°C
	Storing Temperature	-30°C +80°C
	Relative Humidity (No Condensation)	Maks. 95%
EMC-EMI	TS EN 55022, TS EN 55024	
General	Schematics	
	Dimensions	

Avrupa standartlarına uygunluk belgesi - CE Certificate

**Order
Info**

601400 Ethernet Gateway (TCP/IP - RS485)