



Pregled

Vreme isporuke	Usually in Stock
----------------	------------------

Opšte

Obezbeđena oprema	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Number of tare power	41 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Fizički

Dužina kabla	1,48 m
Boja	Black
Dubina	28,8 cm
Visina	22,3 cm
Mounting preference	No preference
Masa proizvoda	9,3 kg
Način montiranja	Ne može se ugraditi u rek
Two post mountable	0
USB kompatibilno	Yes
Širina	14,5 cm

Ulaz

Frekvencija mreže	40...70 Hz
Plug standard	IEC 60320 C14
Ograničenje napona ulaza	100...280 V adjustable (half load) 160...280 V
Inputvolt_other	220 V

	240 V
Broj kablova	1
Naponski ulaz	230 V

Izlaz

Nazivna snaga u w	1600 W
Maximum configurable power in W	1600 W
Izlazna frekvencija	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Mera talasnosti	3 : 1
UPS type	Dvostruka online konverzija
Wave type	Sinusni talas
Nb of power socket outlets	4 IEC 60320 C13
Tip bypass-a	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0,0285
Curve load maximum	100 %
Curve load minimum	4 %
Curve proportional loss	0,0517
Curve square loss	0,0279
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efikasnost	88 % (full load)
Graph display	2
Half load runtime	00:12:00 800 W
Output voltage	230 V
Maximum configurable power in VA	2000 VA
Nazivna snaga u va	2000 VA
Runtime at 400W	00:26:00
Transfer time	4 ms typical

Uskladenost

Sertifikacija proizvoda	CE
Standardi	IEC 62040-1-1 IEC 62040-1-2

Okolina

Temperatura okoline za rad uređaja	0...40 °C
Relativna vlažnost	0...95 % bez kondenzacije
Nadmorska visina za rad	0...10000 ft
Temperatura okoline za skladištenje	-20...50 °C
Storage Relative Humidity	0...95 % Bez kondenzacije
Nadmorska visina skladištenja	0,00...15240,00 m

Nivo zvuka	50 dB
Show note OP temperature	No
IP stepen zaštite	IP20

Baterija i runtime

Tip baterije	Olovna baterija
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 sati
Liquid value	0
Battery curve	D
Battery charger power	76 W rated
Extended runtime	0

Komunikacija i upravljanje

Slobodni slotovi	1
Control panel	Multifunkcionalni LCD status i upravljačka konzola
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Prenaponska zaštita i filtriranje

Surge energy rate	600 J
-------------------	-------

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	10,6 kg
Pakovanje 1 visina	33 cm
Pakovanje 1 širina	23,5 cm
Pakovanje 1 dužina	36,5 cm

Ugovorna garancija

Garancija	2 years repair or replace
-----------	---------------------------