

# Lista sa podacima o proizvodima

## Karakteristike

# SRVS3KIL

## SE Easy UPS SRVS 3000VA 230V sa spoljašnjim baterijskim modulom



### Pregled

|                |                  |
|----------------|------------------|
| Vreme isporuke | Usually in Stock |
|----------------|------------------|

### Opšte

|                                     |   |
|-------------------------------------|---|
| Obezbeđena oprema                   | Basic UPS signalling RS-232 cable<br>CD with software<br>Country-specific detachable power cord<br>1 x DC cable<br>User manual<br>USB cable |
| Number of tare power                | 40 W  |
| Number of power module free slots   | 0   |
| Number of power module filled slots | 0   |
| Redundant                           | No  |
| UPS size                            | WS  |

### Fizički

|                     |                           |
|---------------------|---------------------------|
| Dužina kabla        | 1,52 m                    |
| Boja                | Black                     |
| Dubina              | 42,5 cm                   |
| Visina              | 33,6 cm                   |
| Mounting preference | No preference             |
| Masa proizvoda      | 45,9 kg                   |
| Način montiranja    | Ne može se ugraditi u rek |
| Two post mountable  | 0                         |
| USB kompatibilno    | Yes                       |
| Širina              | 42,5 cm                   |

### Ulaz

|                          |               |
|--------------------------|---------------|
| Frekvencija mreže        | 40...70 Hz    |
| Plug standard            | IEC 60320 C14 |
| Ograničenje napona ulaza | 160...280 V   |

|                 |                |
|-----------------|----------------|
| Inputvolt_other | 220 V<br>240 V |
| Broj kablova    | 1              |
| Naponski ulaz   | 230 V          |

## Izlaz

|                                  |   |
|----------------------------------|---|
| Nazivna snaga u w                | 2400 W  |
| Maximum configurable power in W  | 2400 W  |
| Izlazna frekvencija              | 50/60 Hz +/- 3 Hz sync to mains   |
| Outputvolt_other                 | 220 V<br>240 V  |
| Mera talasnosti                  | 3 : 1   |
| UPS type                         | Dvostruka online konverzija   |
| Wave type                        | Sinusni talas   |
| Nb of power socket outlets       | 6 IEC 60320 C13<br>1 IEC 60320 C19  |
| Tip bypass-a                     | Internal bypass (automatic and manual)  |
| Curve equation                   | Efficiency  |
| Curve fixed loss                 | 0,0229  |
| Curve load maximum               | 100 %   |
| Curve load minimum               | 3 %   |
| Curve proportional loss          | 0,0382  |
| Curve square loss                | 0,0289  |
| Curve X-axis maximum             | 100 %   |
| Curve test cond ID               | Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output. |
| Curve X-axis minimum             | 0 %   |
| Curve X-axis title               | Load  |
| Curve X-axis units               | Percentage  |
| Curve Y-axis maximum             | 100 %   |
| Curve Y-axis minimum             | 50 %  |
| Curve Y-axis title               | Efficiency  |
| Curve Y-axis units               | Percentage  |
| Efikasnost                       | 88 % (full load)  |
| Graph display                    | 2   |
| Half load runtime                | 00:13:00 1200 W   |
| Output voltage                   | 230 V   |
| Maximum configurable power in VA | 3000 VA   |
| Nazivna snaga u va               | 3000 VA   |
| Runtime at 600W                  | 00:31:00  |
| Transfer time                    | 4 ms typical  |

## Usklađenost

|                         |                                |
|-------------------------|--------------------------------|
| Sertifikacija proizvoda | CE                             |
| Standardi               | IEC 62040-1-1<br>IEC 62040-1-2 |

## Okolina

|                                     |                           |
|-------------------------------------|---------------------------|
| Temperatura okoline za rad uređaja  | 0...40 °C                 |
| Relativna vlažnost                  | 0...95 % bez kondenzacije |
| Nadmorska visina za rad             | 0...10000 ft              |
| Temperatura okoline za skladištenje | -20...50 °C               |
| Storage Relative Humidity           | 0...95 % Bez kondenzacije |

|                               |                   |
|-------------------------------|-------------------|
| Nadmorska visina skladištenja | 0,00...15240,00 m |
| Nivo zvuka                    | 50 dB             |
| Show note OP temperature      | No                |
| IP stepen zaštite             | IP20              |

### Baterija i runtime

|                                |   |
|--------------------------------|---|
| Tip baterije                   | Olovna baterija                             |
| Number of battery filled slots | 0   |
| Number of battery free slots   | 0   |
| Battery recharge time          | 4 sati                                      |
| Dodatne informacije            | Podesivo za izlazni napon 220 : 230 ili 240 |
| Liquid value                   | 0   |
| Battery curve                  | D   |
| Battery charger power          | 234 W nazivno                               |
| Extended runtime               | 1   |

### Komunikacija i upravljanje

|                  |  |
|------------------|--|
| Slobodni slotovi | 1  |
| Control panel    | Multifunkcionalni LCD status i upravljačka konzola                                     |
| Alarm            | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

### Prenaponska zaštita i filtriranje

|                   |       |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

### Pakovanje

|                             |         |
|-----------------------------|---------|
| Tip jedinice pakovanja 1    | PCE     |
| Broj jedinica u pakovanju 1 | 1       |
| Pakovanje 1 težina          | 49,8 kg |
| Pakovanje 1 visina          | 46,5 cm |
| Pakovanje 1 širina          | 56,5 cm |
| Pakovanje 1 dužina          | 56,5 cm |

### Ugovorna garancija

|           |                           |
|-----------|---------------------------|
| Garancija | 2 years repair or replace |
|-----------|---------------------------|