



Pregled

Vreme isporuke	Usually in Stock
----------------	------------------

Opšte

Obezbeđena oprema	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Number of tare power	60 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Fizički

Boja	Black
Dubina	37,4 cm
Visina	68,5 cm
Mounting preference	No preference
Masa proizvoda	54 kg
Način montiranja	Ne može se ugraditi u rek
Two post mountable	0
USB kompatibilno	Yes
Širina	19 cm

Ulaz

Frekvencija mreže	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Ograničenje napona ulaza	100...280 V adjustable (half load) 160...280 V
Inputvolt_other	220 V 240 V

Naponski ulaz	230 V
Izlaz	
Nazivna snaga u w	6000 W
Maximum configurable power in W	6000 W
Izlazna frekvencija	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Mera talasnosti	3 : 1
UPS type	Dvostruka online konverzija
Wave type	Sinusni talas
Output connector type	Hard wire 3-wire (H N + E) 1
Tip bypass-a	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efikasnost	94 % (full load)
Graph display	2
Half load runtime	00:10:00 3000 W
Output voltage	230 V
Maximum configurable power in VA	6000 VA
Nazivna snaga u va	6000 VA

Usklađenost

Sertifikacija proizvoda	CE
Standardi	IEC 62040-1-1 IEC 62040-1-2

Okolina

Temperatura okoline za rad uređaja	0...40 °C
Relativna vlažnost	0...95 % bez kondenzacije
Nadmorska visina za rad	0...10000 ft
Temperatura okoline za skladištenje	-15...60 °C
Storage Relative Humidity	0...95 % Bez kondenzacije
Nadmorska visina skladištenja	0,00...15240,00 m
Nivo zvuka	55 dB
Show note OP temperature	No
IP stepen zaštite	IP20

Baterija i runtime

Tip baterije	Olovna baterija
Number of battery filled slots	0
Number of battery free slots	0
Dodatne informacije	Podesivo za izlazni napon 220 : 230 ili 240
Liquid value	0

Battery curve	D
Battery charger power	112400 W nazivno
Extended runtime	0

Komunikacija i upravljanje

Slobodni slotovi	1
Control panel	Multifunkcionalni LCD status i upravljačka konzola
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Da

Prenaponska zaštita i filtriranje

Surge energy rate	600 J
-------------------	-------

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	66 kg
Pakovanje 1 visina	91 cm
Pakovanje 1 širina	29 cm
Pakovanje 1 dužina	49,5 cm

Ugovorna garancija

Garancija	2 years repair or replace
-----------	---------------------------