



### Main

Range	EasyLogic
Device short name	PM2K2AIAO
Product or component type	I/O module
Device application	Optional expansion module
Range compatibility	EasyLogic PM2100 PM2130 EasyLogic PM2200 PM2230

### Complementary

[Ui] rated insulation voltage	2500 V
Number of outputs	2 analog, 4...20 mA
Output voltage	12 V AC
Analogue input type	Analog input (impedance <= 300 Ohm)
Number of inputs	2 analog 4...20 mA
Input voltage	12...30 V AC
Analogue output type	Analog output, impedance <600 Ohm
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Net weight	50 g

### Environment

Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-25...70 °C

### Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	47.3 g
Package 1 Height	5.3 cm
Package 1 width	3.05 cm
Package 1 Length	9.05 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>