



### Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements 2 cable
Power factor	0.9

### Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120/230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch
Luminous flux	1100 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied
Mounting support	Cross rails Metal parts
Fixing mode	Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Length	560 mm
Height	30.5 mm
Colour	Aluminium

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-16...65 °C

## Packing Units

Package 1 Weight	0.340 kg
Package 1 Height	49.000 mm
Package 1 width	54.000 mm
Package 1 Length	595.000 mm

## Offer Sustainability

RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins