



Osnovne informacije

Grupa proizvoda	Prisma
Kompatibilnost grupe proizvoda	Prisma G
Tip proizvoda ili komponente	Šina
Pribor / posebna kategorija	Instalacioni pribor
Tip šine	Modularna Podesiva
Instalirani uređaji	TeSys: fiksno GV2L TeSys: fiksno GV2P TeSys: fiksno GV3 Compact: fiksno NG160 bez zemljospojna zaštita - kontrola: ručica Compact: fiksno NG160 NA bez zemljospojna zaštita - kontrola: ručica Compact: fiksno NG160 sa zemljospojna zaštita - kontrola: ručica ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation Compact: fiksno NSXm sa zemljospojna zaštita - kontrola: ručica - vertikalno instalacija
Opis polova	9 x 3P: fiksno GV2L 9 x 3P: fiksno GV2P 7 x 3P: fiksno GV3 1 x 3P: fiksno NG160 1 x 4P: fiksno NG160 1 x 3P: fiksno NG160 NA 1 x 4P: fiksno NG160 NA 1 x 3P or 4P: fixed NSXm vertical installation

Dopunske informacije

Installation description	Slobodnostojeći orman - širina 600 mm Nadzidni orman - širina 600 mm
Broj vertikalnih modula (50 mm)	3 module(s): GV2L, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2L, direct in 600 mm Widewall-mounted enclosure 3 module(s): GV2P, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2P, direct in 600 mm Widewall-mounted enclosure 5 module(s): GV3, direct in 600 mm Widefloor-standing enclosure 5 module(s): GV3, direct in 600 mm Widewall-mounted enclosure 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widefloor-standing enclosure 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widewall-mounted enclosure

7 module(s): NSXm without earth leakage protection , direct in 600 mm Widefloor-standing enclosure
 7 module(s): NSXm without earth leakage protection , direct in 600 mm Widewall-mounted enclosure
 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widefloor-standing enclosure
 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widewall-mounted enclosure
 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure
 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure
 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widefloor-standing enclosure
 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widewall-mounted enclosure
 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widefloor-standing enclosure
 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widewall-mounted enclosure

9 mm redovi	48
Količina po setu	Set od 1
Visina	58 mm
Širina	467 mm
Dubina	97 mm
Masa proizvoda	0,34 kg
Boja	Prirodna
Materijal	Metal

Okruženje

Standardi	IEC 61439-2 IEC 61439-1
Sertifikacija proizvoda	ASEFA

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	340 g
Pakovanje 1 visina	5,8 cm
Pakovanje 1 širina	10,5 cm
Pakovanje 1 dužina	46,8 cm
Tip jedinice pakovanja 2	BB1
Broj jedinica u pakovanju 2	10
Pakovanje 2 težina	3,78 kg
Pakovanje 2 visina	15 cm
Pakovanje 2 širina	31 cm
Pakovanje 2 visina	48,5 cm
Tip jedinice pakovanja 3	P12
Broj jedinica u pakovanju 3	300
Pakovanje 3 težina	113,4 kg
Pakovanje 3 visina	80 cm
Pakovanje 3 širina	80 cm
Pakovanje 3 visina	120 cm

Održivost ponude

Propis REACH	REACH deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS deklaracija za Kinu

WEEE

Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija

18 meseci
