



Osnovne informacije

Grupa proizvoda	Prisma
Grupa proizvoda	Prisma G
Tip proizvoda ili komponente	Montažna ploča
Pribor / posebna kategorija	Instalacioni pribor
Kompatibilnost grupe proizvoda	Prisma G kablovski vod
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Instalirani uređaji	EasyPact: fixed CVS400 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed INS320...400 - control: direct front rotary handle - vertical installation ComPact: fixed INS500...630 - control: direct front rotary handle - vertical installation ComPact: fixed INV320...400 - control: direct front rotary handle - vertical installation ComPact: fixed INV500...630 - control: direct front rotary handle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS400 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS630 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 with earth leakage protection - control: toggle - vertical installation
Opis polova	1 x 3P: fixed CVS400 vertical installation 1 x 4P: fixed CVS400 vertical installation 1 x 3P: fixed CVS630 vertical installation 1 x 4P: fixed CVS630 vertical installation 1 x 3P: fixed INS320...400 vertical installation 1 x 4P: fixed INS320...400 vertical installation 1 x 3P: fixed INS500...630 vertical installation 1 x 4P: fixed INS500...630 vertical installation 1 x 3P: fixed INV320...400 vertical installation 1 x 4P: fixed INV320...400 vertical installation 1 x 3P: fixed INV500...630 vertical installation 1 x 4P: fixed INV500...630 vertical installation 1 x 3P: fixed NSX400 vertical installation 1 x 4P: fixed NSX400 vertical installation 1 x 3P: fixed NSX630 vertical installation 1 x 4P: fixed NSX630 vertical installation

Odricanje odgovornosti: Ova dokumentacija nije namenjena kao zamena i ne treba je koristiti za utvrđivanje podobnosti ili pouzdanosti ovih proizvoda za određene namene

Condition of using cable tie	Need additional plate (1M high) when installation of device is in vertical
Broj vertikalnih modula (50 mm)	<p>12 module(s): CVS400 without earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): CVS400 without earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): CVS630 without earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): CVS630 without earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>10 module(s): INS320...400, direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>10 module(s): INS320...400, direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): INS500...630, direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): INS500...630, direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>10 module(s): INV320...400, direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>10 module(s): INV320...400, direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): INV500...630, direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): INV500...630, direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): NSX400 without earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): NSX400 without earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): NSX630 without earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>12 module(s): NSX630 without earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>13 module(s): CVS400 with earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>13 module(s): CVS400 with earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>13 module(s): CVS630 with earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>13 module(s): CVS630 with earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>14 module(s): NSX400 with earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>14 module(s): NSX400 with earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p> <p>14 module(s): NSX630 with earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)</p> <p>14 module(s): NSX630 with earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)</p>
Standardi	IEC 61439-2
Sertifikacija proizvoda	ASEFA

Dopunske informacije

Tretman zaštite	Elektroforeza i vruće polimerizovan poliesterski epoksi prah
Završna obrada	Mat Glatko
Boja	Bela (RAL 9001)
Širina	300 mm
Visina	350 mm
Masa proizvoda	0,78 kg
Functional unit	<p>300 mm Prisma G slobodnostojeće kablovsko polje Easycompact CVS400 bez fiksno ručica vertikalno 3P 1 direktno sa dugim poklopcem priključaka 12 216 mm</p> <p>300 mm Prisma G nadzidno kablovsko polje Easycompact CVS400 bez fiksno ručica vertikalno 3P 1 direktno sa dugim poklopcem priključaka 12 216 mm</p> <p>300 mm Prisma G slobodnostojeće kablovsko polje Easycompact CVS400 bez fiksno ručica vertikalno 4P 1 direktno sa dugim poklopcem priključaka 12 216 mm</p> <p>300 mm Prisma G nadzidno kablovsko polje Easycompact CVS400 bez fiksno ručica vertikalno 4P 1 direktno sa dugim poklopcem priključaka 12 216 mm</p> <p>300 mm Prisma G slobodnostojeće kablovsko polje Easycompact CVS630 bez fiksno ručica vertikalno 3P 1 direktno sa dugim poklopcem priključaka 12 216 mm</p>

300 mm Prisma G nadzidno kablovsko polje Compact NSX400 sa fiksno ručica vertikalno 4P 1 direktno sa dugim poklopcem priključaka 14 266 mm
 300 mm Prisma G slobodnostojeće kablovsko polje Compact NSX630 sa fiksno ručica vertikalno 3P 1 direktno sa dugim poklopcem priključaka 14 266 mm
 300 mm Prisma G nadzidno kablovsko polje Compact NSX630 sa fiksno ručica vertikalno 3P 1 direktno sa dugim poklopcem priključaka 14 266 mm
 300 mm Prisma G slobodnostojeće kablovsko polje Compact NSX630 sa fiksno ručica vertikalno 4P 1 direktno sa dugim poklopcem priključaka 14 266 mm
 300 mm Prisma G nadzidno kablovsko polje Compact NSX630 sa fiksno ručica vertikalno 4P 1 direktno sa dugim poklopcem priključaka 14 266 mm

Packing Units

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	780 g
Pakovanje 1 visina	3 cm
Pakovanje 1 širina	22 cm
Pakovanje 1 dužina	23 cm
Tip jedinice pakovanja 2	S04
Broj jedinica u pakovanju 2	25
Pakovanje 2 težina	20,353 kg
Pakovanje 2 visina	30 cm
Pakovanje 2 širina	40 cm
Pakovanje 2 visina	60 cm

Offer Sustainability

Status održive ponude	Green Premium proizvod
Propis REACH	REACH deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS) EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS deklaracija za Kinu Proaktivna RoHS deklaracija za Kinu (izvan RoHS pravnog okvira za Kinu)
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda
Učinak u vezi sa sadržajem halogena	Proizvod sa plastičnim delovima bez halogena

Ugovorna garancija

Garancija	18 meseci
-----------	-----------