

RAPIDUS 211R

Klemsan

606011

Power Factor Controller (1Ø - 12 level)

Category: Energy Management Products

Type: Reactive Power Management

Group: Electronics Products



Commercial Information

Package Unit	1 pcs.
Customs Tariff Number	903289000000
Weight Per Unit Including Packaging	663g

Technical Information

CONNECTION DATA	
Connection Type	Single phase (L-L or L-N) voltage connection with 1 CT
GENERAL	
Measurement System	1Ø
LCD Screen	+
Language Support	Turkish, English, Russian

Password Protection	+
Voltage Transformer Ratio (VTR)	1 - 5000
Current Transformer Ratio (CTR)	1 - 5.000
Number of Measurements in One Period	512
LCD/Screen Refresh Rate	1
Networks	TT, TN, IT
Signal Waveforms	-
Battery	+
Real Time Clock	+
Four Quadrant Measurement	4
Demand Period	1-60 min. adjustable
Phase Diagram	Available
Min./Max./Demand Values	+
COMPENSATION MODES	
Linear	+
Circular	+
Sequential	+
Rapidus (Smart Control Mode)	+
Manual	+
STEP CONFIGURATIONS	
Manual Definition	+
Predefined	1-1-1-1, 1-1-2-2, 1-2-2-4, 1-2-3-3, 1-2-4-4, 1-1-2-4, 1-2-3-4, 1-2-4-8, 1-1-2-3

Power (kVAR)	0.00-1000 adjustable
Type	3Ø capacitor, 3Ø shunt reactor adjustable
DCM	+
Fixed Step Assignment	+
POWER FACTOR SETTINGS	
Target 1 cosØ	0.8 cap. to 0.8 ind. adjustable
Target 2 cosØ	0.8 cap. to 0.8 ind. adjustable
Dual cosØ Target	-
4 Quadrant Operation for Generators	-
ENERGY MEASUREMENT	
Multiple Sub Tariffs (Peak, On-Peak and Off-Peak)	1
1Ø Phase Energy Measurement	-
3Ø Phase Energy Measurement	Available
CURRENT MEASUREMENT INPUT	
Measuring Range	10mA-6A AC
Overvoltage Category	300 V Cat III
Voltage Fluctuation Measurement	2 kV
Power Consumption	<0.2 VA
Intermittent Overload	100A for 1 sec.
Sampling Frequency Between 45-65 Hz	25.6 kHz
VOLTAGE MEASUREMENT INPUT	
Overvoltage Category	300 V Cat III

Measuring Range L-N	95-272 VAC \pm 10%
Measuring Range L-L	164-471 VAC \pm 10%
Frequency Measuring Range	45-65 Hz
Power Consumption	<0.1 VA
Sampling Frequency Between 45-65 Hz	25.6 kHz

POWER QUALITY MEASUREMENTS

THD - Voltage (as %)	+
THD - Current (as %)	+
Harmonics for Current and Voltage Phases	Up to 51st

MEASURING ACCURACY - IEC 61557-12

Total Active Power	Class 0.2
Total Reactive Power	Class 1
Total Reactive Energy	Class 2
Frequency	Class 0.05
Current	Class 0.2
Neutral Current	Class 0.5
Voltage	Class 0.2
Power Factor	Class 0.5
THDV, THDI	Class 1
Total Apparent Power	Class 0.2
Total Active Energy	Class 0.5

MEASURING ACCURACY - IEC 62053-22

Total Active Energy	Class 0.2S
---------------------	------------

MEASURING ACCURACY - IEC 62053-23	
Total Reactive Energy	Class 2
COMPENSATION RELAY OUTPUTS	
Number of Outputs	12
Type	NO (SPST)
Max. Switching Current	2A
Max. Switching Voltage	250VAC
Max. Switching Power	1250VA
Mechanical Operating Life	= 10.0000000 operations
Electrical Operating Life (NO side)	5×10 ⁴ (5A@250VAC) 1×10 ⁵ (5A@30VDC)
ALARM RELAY OUTPUTS	
Number of Outputs	2
Type	NO (SPST)
Max. Switching Current	4A
Max. Switching Voltage	250 VAC
Max. Switching Power	1250 VA
Mechanical Operating Life	= 10.0000000 operations
Electrical Operating Life (NO side)	5×10 ⁴ (5A@250VAC) 1×10 ⁵ (5A@30VDC)
GENERATOR / DAY-NIGHT INPUT	
Number of Inputs	1
Frequency	45-65Hz
Input	95-240VAC
INPUTS AND OUTPUTS	

Digital Outputs	--
Analog Outputs	--
POWER SUPPLY	
Backup Supply Input	--
Voltage	La-Lb den $\pm 10\%$ 95-410VAC
Frequency	45-65Hz
Consumption	< 10VA
MECHANICAL PROPERTIES	
Weight (g)	663
Protection Class	Front IP40 / Rear IP20
Mounting Type	Panel Mount
Packaging Quantity	1
CABLE CROSS-SECTIONS	
Voltage, Current, All Relay Outputs, Generator Input	2.5mm ² - 14AWG with ferrule - 4mm ² - 12AWG without ferrule, 2x1.5mm ² - 2x16AWG
RS485	1.5mm ² - 16AWG with ferrule - 1.5mm ² - 16AWG without ferrule, 2x0.75mm ² - 2x18AWG
ENVIRONMENTAL CONDITIONS	
Operating Temperature	-20°C +55°C
Storage Temperature	-30°C +80°C
Relative Humidity (Non-condensing)	Max. 95%
EMC-EMI	
EN 61000-6-1:2011	+
EN 61000-6-3 - A1 - AC:2013	+

DIAGRAMS

Mains Connection	-
Step Output Connections	-

COMMUNICATION

Protocol	Modbus RTU
Baud Rate	2400-115200 bps adjustable
Parity	---
Stop Bit	1
Slave ID	1-247
Isolation	2000V RMS

CONTROL PROCESS AND FUNCTIONS

Phase Switching Angle	±45 degree adjustable
Average Time	Off, 5 sec, 10 sec, 20 sec, 30 sec, 40 sec, 50 sec, 60 sec adjustable
Step Deactivation Time	1-600 sec. adjustable
Step Discharge Time	3-1000 sec. adjustable
Step Activation Time	1-600 sec. adjustable

TIME RECORDED DATA STORAGE

Alarm Records	50
Hourly Records	1920 Hours x 68 Different Parameters
Daily Records	240 Days x 68 Different Parameters
Monthly Records	36 Months x 68 Different Parameters
Demand	4 Months x 16 Different Parameters