



REX 250, Ethernet Router

REX 250 WiFi, 4 x LAN (Switch)/1 x WAN/1 x WiFi interface

- Remote access to Ethernet-enabled devices such. PLC, HMI, IP camera
- WAN, WIFI, 3G or LTE variants available
- WAN interface for fail-over operation (3G, LTE and Wifi)
- Space saving and compact
- Integrated firewall
- Integrated 4-port LAN switch
- Digital inputs and outputs for connection establishment, status display and alarm
- Easy and fast configuration via the myREX24 VPN portal
- Read, visualize and log data from PLC
- Direct connection of S7-MPI / PROFIBUS devices
- Free S7-MPI / PROFIBUS driver
- Remote control of remote devices via Internet (RS232)
- Remotely maintain USB devices over the Internet

The REX 250 routers are designed for operation in conjunction with the myREX24 V2 portal: The complete parameterization and remote maintenance is carried out via the portal. In addition to remote maintenance, the REX 250 routers can also read data from the PLC, visualize and generate alarms. For remote maintenance and data transmission, the industrial router uses an encrypted VPN tunnel based on the secure OpenVPN protocol. The REX 250 routers also enable remote maintenance and data access to PLCs via an MPI / PROFIBUS and via an RS232 interface. With the 4 digital inputs, alarms can be sent via SMS and email via the myREX24 V2 Portal. The 2 digital outputs can change the system states of the router, e.g. with a lamp on the control cabinet, or can be activated via the portal. The USB host interface available on all devices enables the connection of USB device devices (eg programming interface of a drive) via the remote maintenance tunnel (USB-over-IP).

The REX 250 WiFi establishes the connection to the myREX 24 V2 portal via WLAN. Additional Ethernet devices can be connected to the router via the integrated 4-port switch. For data transmission, our industrial router uses an encrypted VPN tunnel based on the secure OpenVPN protocol.

Technical specifications

General information	
Order number	700-878-WIF02
Article name	REX 250 WiFi, 4 x LAN (Switch)/1 x WAN/1 x WiFi
Scope of delivery	REX 250 WiFi, Quick Start Guide
Dimensions (DxWxH)	35 x 100 x 73 mm
Weight	Approx. 250 g
Digital inputs Type	4 pieces DIN EN 61131-2 Type 3
Digital outputs electricity	2 pieces max. 0.5 A for each output
WAN interface	
Number	1
Type	10-Base-T/100-Base-T
Connection	RJ45 socket
Transmission rate	10/100 Mbps
LAN interface	

Number	4
Type	10-Base-T/100-Base-T
Connection	RJ45 socket
Transmission rate	10/100 Mbps
USB interface	
Number	1
Protocol	USB 2.0 Host
Connection	USB-A-socket
Serial Interface	
Type	RS-232/422/485 (software switchable)
Protocol	transparent access via virtual COM port
Transmission rate	300 bauds ... 115 k bauds
PROFIBUS interface	
Transmission rate	up to 12 Mbps
Interface	RS-232/485 (software switchable)
Connection	Socket, SUB-D, 9-pin
Status indicator	4 LEDs, function status 8 LEDs, Ethernet status
Voltage supply	24 V DC, 18... 28 V DC
Current draw	max. 100 mA @ DC 24 V
VPN	
VPN protocol	IPsec/PPTP/OpenVPN, 64 tunnels
Encryption Method	Blowfish, AES, DES/3DES
Encryption algorithms	MD5, SHA1
Authentication	Pre-shared key, X.509
Network/security	
Firewall	1:1 NAT, IP filter, port forwarding, stateful inspection
IP router	NAT IP, TCP/IP routing, IP forwarding
Services	DHCP server, DHCP client, DNS server, NTP client, PPP server, DynDNS
Time comparison	NTP server
Ambient conditions	
Ambient temperature	-40 °C ... +75 °C
Transport and storage temperature	-40 °C ... +85 °C
Relative air humidity	0 – 95% non-condensing
Pollution degree	2
Protection rating	IP20
Certifications	CE
CE	
RoHS	Yes
REACH	Yes