



Osnovne informacije

Grupa proizvoda	TeSys
Ime proizvoda	TeSys D
Tip proizvoda ili komponente	Kontaktora za promenu smera
Kratko ime uređaja	LC2D
Primena kontaktora	Rezistivno opterećenje Upravljanje motorom
Kategorija upotrebe	AC-3 AC-1
Prezentacija uređaja	Prefabrikovan sa promenom redosleda faza
Broj polova	3P
Power pole contact composition	3 NO
[Ue] nazivni napon	Power circuit: \leq 1000 V AC 25...400 Hz Power circuit: \leq 300 V DC
[Ie] nazivna struja	125 A (at \leq 60 °C) at \leq 440 V AC AC-1 for power circuit 80 A (at \leq 60 °C) at \leq 440 V AC AC-3 for power circuit
Snaga motora kw	22 kW pri 220...230 V AC 50 Hz 37 kW pri 380...400 V AC 50 Hz 45 kW pri 415...440 V AC 50 Hz 55 kW pri 500 V AC 50 Hz 45 kW pri 660...690 V AC 50 Hz 45 kW pri 1000 V AC 50 Hz
Motor power HP (UL / CSA)	20 hp pri 200/208 V AC 60 Hz za trofazne motori 7,5 hp pri 115 V AC 60 Hz za monofazne motori 15 hp pri 230/240 V AC 60 Hz za monofazne motori 25 hp pri 230/240 V AC 60 Hz za trofazne motori 60 hp pri 460/480 V AC 60 Hz za trofazne motori 60 hp pri 575/600 V AC 60 Hz za trofazne motori
Tip upravljačkog kola	AC at 50/60 Hz
Napon upravljačkog kola	24 V AC 50/60 Hz
Sastav pomoćnog kontakta	1 NO + 1 NC

Odricanje odgovornosti: Ova dokumentacija nije namenjena kao zamena i ne treba je koristiti za utvrđivanje podobnosti ili pouzdanosti ovih proizvoda za određene namene

[Uimp] nazivni podnosivi impulsni napon	8 kV conforming to IEC 60947
Kategorija prenapona	III
[Ith] dozvoljena termička struja u vazduhu	10 A (at 60 °C) for signalling circuit 125 A (at 60 °C) for power circuit
Irms nazivna moć uključenja	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1100 A at 440 V for power circuit conforming to IEC 60947
Nazivna prekidna moć	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] kratkotrajna podnosiva struja kratkog spoja	135 A 40 °C - 10 min for power circuit 320 A 40 °C - 1 min for power circuit 640 A 40 °C - 10 s for power circuit 990 A 40 °C - 1 s for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Pripadajući osigurač	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Prosečna impedansa	0.8 mOhm - Ith 125 A 50 Hz for power circuit
[Ui] nazivni napon izolacije	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1
Električna trajnost	0,8 miliona ciklusa 125 A AC-1 pri Ue <= 440 V 1,5 miliona ciklusa 80 A AC-3 pri Ue <= 440 V
Snaga disipacije po polu	12.5 W AC-1 5,1 W AC-3
Front cover	Sa
Tip blokade	Mehanička
Nosači za montažu	Ploča Šina
Standardi	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Sertifikacija proizvoda	GOST LROS (Lloyds register of shipping) CCC GL CSA RINA UL BV DNV
Povezivanje - priključci	Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² solid Control circuit: screw clamp terminals 2 cable(s) 1...4 mm ² solid Control circuit: screw clamp terminals 1 cable(s) 1...2.5 mm ² flexible with cable end Power circuit: connector 1 cable(s) 4...50 mm ² flexible without cable end Power circuit: connector 2 cable(s) 4...25 mm ² flexible without cable end Power circuit: connector 1 cable(s) 4...50 mm ² flexible with cable end Power circuit: connector 2 cable(s) 4...16 mm ² flexible with cable end Power circuit: connector 1 cable(s) 4...50 mm ² solid Power circuit: connector 2 cable(s) 4...25 mm ² solid
Moment pritezanja	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm
Vreme uključenja/isključenja	20...35 ms zatvaranje 6...20 ms otvaranje

Nivo sigurnosne pouzdanosti	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mehanička trajnost	4 miliona ciklusa
Maksimalni radni ciklus	3600 cyc/h 60 °C

Dopunske informacije

Tehnologija kalema	Bez ugrađenog prigušivača
Ograničenje napona upravljačkog kola	0.3...0.6 Uc (-40...70 °C):drop-out AC 50/60 Hz 0.8...1.1 Uc -40...55 °C u radu AC 50 Hz 0.85...1.1 Uc -40...55 °C u radu AC 60 Hz 1...1.1 Uc 55...70 °C u radu AC 50/60 Hz
Udarne snaga u va	245 VA 60 Hz 0,75 20 °C) 245 VA 50 Hz 0,75 20 °C)
Snaga držanja u va	26 VA 60 Hz 0,3 20 °C) 26 VA 50 Hz 0,3 20 °C)
Disipacija toplote	6...10 W pri 50/60 Hz
Tip pomoćnog kontakta	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Frekvencija signalnog kola	25...400 Hz
Minimalna struja preklapanja	5 mA for signalling circuit
Minimalni napon preklapanja	17 V for signalling circuit
Vreme nepreklapanja	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Otpornost izolacije	> 10 MOhm for signalling circuit

Okruženje

Ip stepen zaštite	IP20 front face conforming to IEC 60529
Zaštitni tretman	TH conforming to IEC 60068-2-30
Stepen zaprljanosti	3
Temperatura okoline za rad	-40...60 °C 60...70 °C with derating
Temperatura okoline za skladištenje	-60...80 °C
Nadmorska visina za rad uređaja	0...3000 m
Otpornost na vatru	850 °C u skladu sa IEC 60695-2-1
Otpornost na plamen	V1 conforming to UL 94
Mehanička robusnost	Vibrations contactor open: 2 Gn, 5...300 Hz Shocks contactor open: 8 Gn for 11 ms Vibrations contactor closed: 3 Gn, 5...300 Hz Shocks contactor closed: 10 Gn for 11 ms
Visina	127 mm
Širina	182 mm
Dubina	158 mm
Masa proizvoda	3,2 kg

Pakovanje

Tip jedinice pakovanja 1	PCE
Broj jedinica u pakovanju 1	1
Pakovanje 1 težina	3,735 kg
Pakovanje 1 visina	19 cm
Pakovanje 1 širina	20 cm
Pakovanje 1 dužina	25,5 cm
Tip jedinice pakovanja 2	S03
Broj jedinica u pakovanju 2	2
Pakovanje 2 težina	7,918 kg
Pakovanje 2 visina	30 cm

Pakovanje 2 širina	30 cm
Pakovanje 2 visina	40 cm

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS deklaracija za Kinu Proaktivna RoHS deklaracija za Kinu (izvan RoHS pravnog okvira za Kinu)
Izjava o zaštiti okoliša	Profil ekološke prihvatljivosti proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Bez PVC	Da

Ugovorna garancija

Garancija	18 months
-----------	-----------