

Z1T-SD-500

Klemsan

261022

Timer Relay

Category: Protection and Control Relays

Type: Star-Delta Relay

Group: Electronics Products



Commercial Information

Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	0,08

Technical Information

GENERAL	
Connection Type	Screw terminal
Protection Class	IP20
Weight (g)	80
Case Width (mm)	18
Mounting Type	Panel & Rail

Supply Frequency	45-65 Hz
Output Type	Relay
Functions	SD
Restore Time	Maks. 100ms
Trigger Input Voltage	---
POWER SUPPLY	
Voltage	150-500 VAC
Power Consumption	<1,5W DC / <10VA AC
ENVIRONMENTAL CONDITIONS	
Operating Temperature	-20 to + 60°C
Storage Temperature	-40°C +75°C
Relative Humidity (Non-condensing)	Max. 95%
BACKUP CONNECTIONS	
Type	2 C/O (SPDT)
Max. Values - AC (NO side)	16A/250V; 2000VA
Max. Values - DC (NO side)	5A/30VDC; 150W
Mechanical Operating Life	= 10 ⁷ operations
Electrical Operating Life (NO side)	5x10 ⁴ (5A@250VAC) 1x10 ⁵ (5A@30VDC)
TIME INTERVAL	
Timing 1	0,1 sn .. 30 sn
Timing 2	20 msn .. 500 msn